EGM	SCM	CORPORATION
EGM	SCM	CORPORATION

EN COATINGS & RESINS DIVISION
ICLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE NO. (216) 826-5566

LASH POINT (SETA)

OT (PSN)

AZARD CLASS

104 F

PAINT, UN 1263

COMBUSTIBLE LIQUID

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

**∑**20

PAGE

1

	SECTION I				
ODE IDENTIFICATION RODUCT IDENTIFICATION	DATE PI	RINTED C GLOSS /sp.	02/14/86	÷	
******	SECTION II - HAZARDOUS IN	GREDIENTS			
INGREDIENT .	WEIGHT PERCENT T	HRESHOLD LIMIT VA	LUE LEL	VAPOR PRESS.	
INERAL SPIRITS CAS NO	. 29 64742-88-7	100 PPM	<b>*</b> 1.0	7+00	
INERAL SPIRITS, ) CAS NO	JARROW RANGE 23 64742-88-7	200 PPM	⇒ 1.0	2.50	
⇒ NONE ESTABLISHED BY ACGIH. VALUE SHOWN IS TYPICALLY RECOMMENDED BY SUPPLIERS.  THE THRESHOLD LIMIT VALUE (TLV) IS THE TIME WEIGHTED AVERAGE (TWA) TO WHICH IT IS BELIEVED THAT HOST WORKERS MAY BE EXPOSED 8-10 HOURS PER DAY, 40 HOURS PER WEEK WITHOUT ADVERSE HEALTH EFFECTS.  LEL - THE LOWER EXPLOSIVE LIMIT IS THE LOWEST CONCENTRATION (% OF VOLATILES IN AIR) THAT WILL PRODUCE A FLASH OF FIRE WHEN AN IGNITION SOURCE IS PRESENT.					
***	SECTION III - PHYSICAL DAT	 A			
OILING RANGE VOLATILE BY VOL	313 - 374 F WEIGHT JME 59•73	PER GALLON	7.39		
1	SECTION IV - FIRE AND EXP	LOSION HAZARD DAT	A		

LOWER EXPLOSIVE LIMIT

SCM CORPORATION

EN COATINGS & RESINS DIVISION JCLID AVENUE CLEVELAND, OHIO 44115 EMERGENCY TELEPHONE NO. (216) 826-5566 The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

SECTION IV FIRE AND EXPLOSION HAZARD DATA

EXTINGUISHING MEDIA

DRY CHEMICAL OR FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE.

VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES.

MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR TOXIC GASES.

SPECIAL FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.

SECTION V

- HEALTH HAZARD DATA

ROUTE OF ENTRY

INHALATION SKIN EYES . INGESTION

EFFECTS OF OVEREXPOSURE

IRRITATION OF EYES, SKIN, RESPIRATORY TRACT, PROLONGED INHALATION MAY LEAD TO FATIGUE, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, CENTRAL NERVOUS SYSTEM DEPRESSION. PROLONGED OR REPEATED CONTACT CAN CAUSE DERMATITIS, DEFATTING, BLURRED VISION, TEARING OF EYES, REDNESS OF EYES, POSSIBLE NAUSEA, VOMITING, DIARRHEA, BLURRED VISION, TEARING OF EYES, ANESTHETIC EFFECT OR NARCOSIS, DIFFICULTY OF BREATHING, UNCONSCIDUSNESS. NOTICE - REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

RGENCY AND FIRST AID PROCEDURES



EN COATINGS & RESINS DIVISION

JCLID AVENUE

CLUVELAND, OHIO 44115

EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

20

PAGE

3

	SECTION V - HEALTH HAZARD DATA			
INHALATION	MOVE PERSON TO WELL VENTILATED AREA.  GET EMERGEMCY MEDICAL ATTENTION.  ADMINISTER DXYGEN OR ARTIFICIAL RESPIRATION IF NECESSARY.			
SKIN. CONTACT	FLUSH FROM SKIN WITH WATER, THEN WASH THOROUGHLY WITH SDAP AND WATER. REMOVE CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING DEFORE RE-USE.			
EYE CONTACT	FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET EMERGENCY MEDICAL ATTENTION.			
INGESTION	GET EMERGENCY MEDICAL ATTENTION.			
	SECTION VI - REACTIVITY DATA			
LITY	STABLE			
COMPATIBILITY	OXIDIZERS ACIDS BASES			

CONDITIONS TO AVOID

ELEVATED TEMPERATURES
CONTACT WITH OXIDIZING AGENT

MAZARDOUS DECOMPOSITION PRODUCTS

ACIXONOM NOGRAD

BOIXOID NOGRAD

AMINES \*

MAZARDOUS POLYMERIZATION

WILL NOT OCCUR



CLID AVENUE
CLL VELAND, OHIO 44115
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

20

PAGE

SECTION VII - SPILL OR LEAK PROCEDURES

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA.

SMALL SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS. LARGE SPILLS - DBSERVE STEPS FOR SMALL SPILLS. SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGE MATERIAL AND RINSE WATER DUT OF SEWERS OR WATER COURSES. COMPLY WITH ALL APPLICABLE REGULATIONS FOR HEALTH AND POLLUTION CONTROL.

MASTE DISPOSAL

DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. .AVOID DISCHARGE TO NATURAL WATERS.

SECTION VIII - SPECIAL PROTECTION INFORMATION

LIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE STANDARDS. WHERE RESPIRATORY PROTECTION IS REQUIRED, USE ONLY NIOSH/MSHA APPROVED RESPIRATORS IN ACCORDANCE WITH OSHA STANDARD 29 CFR 1910.134.

'ENTILATION

PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

'ERSONAL PROTECTIVE EQUIPMENT

EYE WASH
SAFETY SHOWER
-SAFETY GLASSES OR-GOGGLES
IMPERVIOUS GLOVES

SECTION IX - SPECIAL PRECAUTIONS

ANDLING AND STORAGE

STORE BELOW 100 F.
KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.





9 CLID AVENUE CLL -ELAND, OHIO 44115 EMERGENCY TELEPHONE NO. (216) 826-5566 The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

20

PAGE

5

SECTION IX - SPECIAL PRECAUTIONS

ITHER PRECAUTIONS

USE ONLY WITH ADEQUATE VENTILATION.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE

EATING OR SMOKING.

KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.

EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.